

NOTES A3 SHEET SIZE SERVICES KEY E1 63AMP SINGLE PHASE COMMANDO E2 E2 32AMP SINGLE PHASE COMMANDO
-11 🚬
E2 32AMP SINGLE PHASE COMMANDO
E3 63AMP THREE PHASE COMMANDO
E4 32AMP THREE PHASE COMMANDO
E5 E5 13AMP SINGLE PHASE PLUG
E6 E6 100AMP THREE PHASE HARD WIRED
E7 80AMP THREE PHASE HARD WIRED
E8 16AMP SINGLE PHASE COMMANDO
W1 W1 15MM BSP WATER INLET
W2 22MM BSP WATER INLET
W3 22MM BSP HOT WATER INLET
W4 15MM BSP HOT WATER INLET
F1 F1 40MM BSP WASTE OUTLET
F2 F2 100MM BSP FOUL WASTE OUTLET
F3 50MM BSP WASTE OUTLET
F4 F4 32MM BSP WASTE OUTLET
F5 F5 110MM BSP WASTE OUTLET
G1 NAT GAS / LPG INLET
COMMANDO PLUG AND SOCKET SUPPLIED BY MKL WATER PRESSURE REQUIRED 1.5 TO 6 BAR
WATER SOFTENING REQUIRED TO HARD WATER AREAS MANULLY OPERABLE GAS VALVE NEEDS TO BE LOCATED IN A READLY ACCESSIBLE POSITION NEAR A KITCHEN EMERGENCY EXIT; IF THIS IS NOT PRACTICABLE AN EMERGENCY STOP MUST BE INSTALLED IN THIS POSITION AND WIRED BACK TO AN ELECTRC ISOLATION VALVE.
FIRST ISSUE REV DATE DESCRIPTION DRAWN CLIENT SAMPLE PROJECT SAMPLE TITLE GENERAL ARRANGEMENT STATUS DESIGN DEVELOPMENT ORIGINATOR JH CREATED ON 30.03 2017 STORE 3.8M - REVISION CONSTRUCTION REVISION